



Valueklave™1730

Valueklave 1730





Speed, Quality & Value

- Fast cycle time, 11 minutes from a hot start (Standard Unwrapped Cycle Time)
- Efficent drying cycle for wrapped instruments
- Contemporary design with easy to read panel
- Economically priced a compact size

Valueklave™1730

The Valueklave[™]1730 will satisfy all of your basic sterilization needs at an economical price. High speed and reliability are built into every Valueklave[™] 1730.



| Fea | itur | PS. |
|-----|------|-----|
| | , | CJ. |

- Fast Cycle Time. 11 minutes from a hot start* (Standard Unwrapped Cycle time).
- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Overheat cutoff prevents burnout of heating elements in case of insufficient water in the chamber.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications.

| Valueklave™ 1730 Specification | | |
|--------------------------------|--------------------|--|
| Chamber Dimensions | 7"x13" | |
| 0 x L in (mm) | (170 X 340) | |
| Volume | 2 gal/7.5 L | |
| Overall Dimensions | 17.9"x 17.4 "x 12" | |
| DxWxH in (mm) | (455 x 440 x 305) | |
| Standard Cassettes | 2 half | |
| Tray Dimensions | 11.6"x 4.7 "x 0.8" | |
| DxWxH in (mm) | (295 x 120 x 20) | |
| No. of Trays | 3 | |
| Standard Unwrapped | Cold: 16 min | |
| Cycle Time | Hot: 11 min | |
| Voltage (V) | 120 | |
| Freq. (Hz) | 50/60 | |
| Power (W) | 1350 | |
| Curret (A) | 11 | |
| Shipping Weight lbs (kg) | 55 (25) | |



*Come up time, sterilization exposure and exhaust



Clean&Simple™ Ultrasonic Cleaners and Tablets



Steam Distiller



Chamber Brite Autoclave Cleaner









CANADIAN MEDICAL & SURGICAL SUPPLIES EMAIL: alnewman.cmss@gmail.com

